NOVAH®

Nobius 3.0 – Product Technical Specifications

	Nobius Cove (Single Standing Unit)	Nobius Cove (Single Sitting Unit)
Acoustic Performance	Class A+（ISO 23351），DS,A 33.2dB；	
Main Frame Materials	Frame: 6063-T5 Aluminum Profile Steel Components: SPCC Cold-Rolled Steel with Electrostatic Powder Coating	
Dimensions	**W * D * H (mm)**	
Internal Dimensions	W950*D900*H2090	
External Dimensions	W1100*D1000*H2290	
Net Weight (without furniture)	340KG	
Unit Net Weight (without furniture)	309Kg/m²	
Gross Weight (with packaging)	400KG	
Electrical Power (China Standard)	Max 100W	
Packaging	W2200*D600*H1200	
Soundproof Wall Structure	Wall Panel Design: Multi-layer sound insulation and vibration reduction structure Layer Composition: 6 layers	
Interior Soft Panel Material	Wall Padding: 30mm High-Density Molded Foam with Fabric Upholstery	
Carpet Material	Flooring: 10mm Flame-Retardant & Stain-Resistant Nylon Carpet (Black)	
Glass Door	4+4mm Tempered Laminated Glass	
Rear Glass	4+4mm Tempered Laminated Glass	
Door Handle	Handle Type: Magnetic Handle	
Network Connectivity	Socket Options: Wall-mounted socket with single/dual Ethernet port configuration	
Recommended Configuration	Nobius Cove – Standing Unit	Nobius Cove – Sitting Unit
Tabletop Specification	Material: Plywood with 45° Beveled Edge Finish Options: LB Obsidian Black LW Arctic White LO Oak Finish Edge Treatment: Wood Wax Oil Sealing Dimensions: Standing Tabletop: W868 × D350 × H25 mm; Height: 1080 mm	Material: Plywood with 45° Beveled Edge Finish Options: LB Obsidian Black LW Arctic White LO Oak Finish Edge Treatment: Wood Wax Oil Sealing Dimensions: Sitting Tabletop: W868 × D350 × H25 mm; Height: 730 mm
Standard Seating	Nobius Rocking Stool Dimensions: W410 × D410 × H575–720 mm Load Capacity: 200 kg Gas Lift: SGS Certified Net Weight: 4.7 kg	Single Sofa Dimensions: W950 × D860 × H770 mm Seat Height: 420 mm Seat Depth: 450 mm
Power Outlets	Fan Quantity & Size: 1 x Ø250 mm Silent Fan	Fan Quantity & Size: 1 x Ø250 mm Silent Fan
Ventilation System	1 x Ø250 mm Silent Fan	1 x Ø250 mm Silent Fan
Occupancy Sensor	Sensor Type: Infrared Motion Sensor Control Functions: Automatically controls fan and lighting system based on presence detection	
Lighting Specification	LED Lighting: 2 x 0.855m LED Strip (15W/m) Color Temperature: 5000K (Natural White) Flicker-Free Light Source	
Ventilation System	Airflow Rate: 2.4 m³/min Air Circulation Time: Every 43 seconds Fan Model: Voltage: 12V / 1A RPM: 900 Airflow: 108 CFM Pressure: 1.63 mmH_2O Noise Level: 38 dB(A)	
Mobility Features	Footwheel Type: Horse-Shoe Anti-Slip Casters Quantity: 4 Adjustable & Lockable Casters per Unit	Footwheel Type: Horse-Shoe Anti-Slip Casters Quantity: 4 Adjustable & Lockable Casters per Unit